This listing of claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims:**

1. (Currently Amended) A coin processing device, comprising: a housing;

a disk-type coin sorter disposed within the housing, the coin sorter comprising
an input hopper for receiving coins of a plurality of denominations to be sorted,
a rotatable disk for imparting motion to the plurality of coins, and

a stationary head having a lower surface generally parallel to and spaced slightly away from the rotatable disk, the lower surface having a plurality of shaped regions for controlling [[the]] movement of the coins and guiding coins to a plurality of exit channels for discharging coins, the plurality of coin exit channels corresponding to a plurality of coin denominations to be processed, [[and]]

a coin receptacle station disposed within the housing for holding a plurality of coin receptacles, each of the plurality of receptacles for holding coins of a single denomination, the coin receptacle station being moveable between a first position and a second position, the coin receptacle station being disposed entirely within the housing for receiving coins when in the first position, the coin receptacle station having a manifold including a plurality of coin paths for guiding coins from the exit channels to the coin receptacles when the coin receptacle station is in the first position, the coin receptacle station extending out of the housing when in the second position; and

a dampening mechanism configured to control the movement of the coin receptacle station between the first position and the second position.

- 2. (Currently Amended) The coin processing device of claim 1, wherein the coin receptacle station includes a plurality of casters, the coin receptacle station being adapted to roll on the plurality of casters when moving between the first position and the second position.
- 3. (Currently Amended) The coin processing device of claim 1, wherein the coin receptacles comprise coin bags, the coin receptacle station including a plurality of coin bag

Application No. 10/797,839
 Response to Office Action Dated February 28, 2007

holders.

4. (Currently Amended) The coin processing device of claim 1, further comprising

wherein a dampening mechanism for controlling the movement of the coin receptacle station

between the first position and the second position, the dampening mechanism having comprises a

first end coupled to the housing and a second end coupled to the coin receptacle station.

5. (Currently Amended) A coin processing machine, comprising:

a housing [[for]] containing [[the]] a coin processing device;

a coin processing unit disposed within the housing, the coin processing unit adapted to

process received coins of a plurality of denominations and to discharge processed coins into a

plurality of coin receptacles; [[and]]

a coin receptacle station disposed within the housing for holding a plurality of coin

receptacles, the coin receptacle station including a plurality of individually moveable platforms

each having at least one coin receptacle disposed thereon, each moveable platform being

moveable between a first position and a second position, each moveable platform being disposed

entirely within the housing for receiving coins in the at least one coin receptacle disposed thereon

when in the first position, each moveable platform extending out of the housing when in the

second position, and

a track along which each moveable platform rides when moving between the first position

and the second position.

6. (Cancelled) The coin processing device of claim 5 further comprising a track

along which each moveable platform rides when moving between the first position and the

second position.

7. (Currently Amended) The coin processing device of claim 5, wherein the coin

processing unit comprises a disk-type coin sorter having a plurality of coin exit channels for

discharging sorted coins.

3

- 8. (Currently Amended) The coin processing device of claim 7, wherein the coin receptacle station comprises a manifold having a plurality of coin paths for directing coins discharged from the plurality of exit channels to the plurality of coin receptacles.
- 9. (Currently Amended) The coin processing device of claim 8, wherein the coin receptacles are coin bins.
- 10. (Currently Amended) The coin processing device of claim 8, wherein the coin receptacles are coin bags.
- 11. (Currently Amended) The coin processing device of claim 10, wherein each of the moveable platforms include at least one coin bag partition for separating the coin bags.
- 12. (Currently Amended) The coin processing device of claim 10 wherein the coin receptacle station includes a plurality of coin bag holders disposed proximate [[the]] exits of the plurality of coin exit channels [[paths]].
- 13. (Currently Amended) The coin processing device of claim 5, wherein the coin receptacles are coin bags.
- 14. (Currently Amended) The coin processing device of claim 5, wherein the housing further comprises a door moveable between an open position and a closed position, the door permitting a moveable platform to move from the first position to the second position when the door is in the open position.
- 15. (Currently Amended) The coin processing device of claim 14, wherein the door is disposed on the rear side of the housing.
- 16. (Currently Amended) The coin processing device of claim 14, wherein the door is disposed on the front side of the housing.

## 17-24 (Cancelled).

25. (Currently Amended) A method for processing coins with a coin processing machine includes comprising a housing, a coin sorting unit disposed within the housing, and a plurality of moveable coin receptacle coin receptacle platforms each for holding at least one coin receptacle, the coin receptacle coin receptacle platforms each being independently moveable between a first position and a second position, each coin receptacle coin receptacle platform being disposed entirely within the housing for receiving coins when in the first position, each coin receptacle coin receptacle platform extending out of the housing when in the second position, the method comprising:

receiving a plurality of coins of a plurality of denominations to be sorted;

sorting the plurality of coins according to denomination with the coin sorting unit;

directing sorted coins to the plurality of <u>moveable</u> coin receptacles, each coin receptacle containing coins of a single denomination; and

moving one of the <u>plurality of moveable coin receptacle</u> eoin receptacle platforms from the first position to the second position for accessing the coin receptacles.

- 26. (Currently Amended) The method of claim 25, further comprising: opening a door of the housing prior to moving the one of the eoin-receptacle coin receptacle platforms from the first position the second position.
  - 27. (Currently Amended) A coin processing device, comprising:
  - a housing for containing the coin processing device;
- a coin sorting unit disposed within the housing, the coin sorting unit <u>being configured to</u> sorting <u>sort</u> and <u>discharging discharge</u> coins according to denomination; [[and]]

a coin receptacle area <u>comprising</u> selected from the group consisting of a coin receptacle station disposed within the housing for holding a plurality of coin receptacles each for receiving discharged coins of a single denomination, the coin receptacle station including a plurality of individually moveable platforms each having at least one coin receptacle disposed thereon, each moveable platform being moveable between a first position and a second position, each

moveable platform being disposed entirely within the housing for receiving coins in the at least one coin receptacle disposed thereon when in the first position, each moveable platform extending out of the housing when in the second position, and

a moveable coin bin for receiving the discharged coins and commingling the received coins in an interior of the coin bin a track upon which each of the plurality of individually moveable platforms is disposed to move between said first position and said second position.

- 28. (Cancelled) The coin processing device of claim 27 wherein the moveable coin bin is disposed on wheels.
- 29. (Cancelled) The coin processing device of claim 27 comprising a telescoping handle pivotally attached to the movable coin bin has a telescoping handle.
- 30. (Currently Amended) The coin processing device of claim 27, wherein the coin receptacles comprise coin bags.
- 31. (Currently Amended) The coin processing device of claim 28, <u>further</u> comprising at least one coin bag partition disposed on each of the moveable platforms.
- 32. (Cancelled) A method for manufacturing a coin processing device based on the needs of a customer, the method comprising:

providing a coin processing device having a housing containing a coin processing unit for processing received coins and discharging coins to a coin receptacle area disposed within the housing, the coin receptacle area being cabling of receiving one of

a coin receptacle station disposed within the housing for holding a plurality of coin receptacles each for receiving discharged coins of a single denomination, the coin receptacle station including a plurality of individually moveable platforms each having at least one coin receptacle disposed thereon, each moveable platform being moveable between a first position and a second position, each moveable platform being disposed entirely within the housing for receiving coins in the at least one coin receptacle disposed thereon when in the first position,

each moveable platform extending out of the housing when in the second position, or

a moveable coin bin for receiving the discharged coins and commingling the received coins in an interior of the coin bin;

selecting, based on customer input, one of the coin receptacle station or the moveable coin bin; and

installing the selected one of coin receptacle station or the moveable coin bin based on customer input.

- 33. (New) The coin processing device of claim 27, wherein each track comprises a stationary first member having a trapezoidal cross-sectional profile and each individually moveable platform comprises a substantially mating profile.
- 34. (New) The coin processing device of claim 27, wherein, in said second position, said individually moveable platform is substantially cantilevered relative to said track.